




Que-2-TXT™  
Questions?  
scan to text us fast



# HIGH BAY LINEAR LED FIXTURE



2' X 4'

HID equal

## specifications

Lens	CRI	Finish	Material	L70 hours	SP	Ambient Temp (F)	Power Factor	UL listing	THD	Dimensions
polycarbonate	>70	white	die-cast aluminum	50,000	10 KV optional	-40° - 131°	> 0.9	damp location	<0.2	47.5" x 24" x 2.97"

Part Number	Color Temp	Voltage	Consumption	Lumen Output	Efficacy	Weight
GI-24LHB-C1000EC-UL4	5000K	120 - 277 V	270 W	36,000	133 LM / W	23.70 lbs
GI-24LHB-C1000-UL4	5000K	120 - 277 V	300 W	40,000	133 LM / W	25.00 lbs
GI-24LHB-D1000-UL4	4000K	120 - 277 V	300 W	40,000	133 LM / W	25.00 lbs
GI-24LHB-C1000-480UL4	5000K	347 - 480 V	300 W	40,000	133 LM / W	25.00 lbs

## select your accessories\*

Part Number	Description
GI-ACC-OCC	occupancy sensor
GI-ACC-EB	emergency battery back up kit
GI-ACC-WG	wire guard
GI-ACC-PH	pendant hanger

## other


Warranty	Case QTY
1 year	1 pc




## Features

- Suitable for commercial, retail and industrial applications.
- Chain, pendant and surface mounting available.
- Standard 1-10V dimming.


## Vertical Isolux Plot



## Distance vs Illumination



## Luminous Intensity Diagram



Not all product variations listed on this page may be DLC qualified. Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification.



/greenignite  
@greenignite



www.greenignite.com



info@greenignite.com



1-877-560-3779