



Que-2-TXT™  
Questions?  
scan to text us fast



LINEAR BATTEN LED LAMP



STANDARD OUTPUT LINKABLE fluorescent equal

specifications

Consumption	Lumen Output	Efficacy	Lens	Heat Sink	L70 hours	Ambient Temp (F)	Power Factor	UL listing	CRI	THD	Dimensions
12W	1,500	125 LM/W	polycarbonate	aluminum	50,000	-4° - 113°	>0.9	IP40	83	<20%	35.43" x 1.53" x 1.65"

select your lamp

Part Number	Color Temp	Voltage
GI-3T8D-W30-BF	3000K Frosted DIM	120 VAC ⚡
GI-3T8-D30-BF	4000K DIM	100 - 277 V ⚡
GI-3T8-D30-BC	4000K	100 - 277 V ⚡
GI-3T8-C30-BC	5000K	100 - 277 V ⚡

Frosted frosted DIM dimmable (line voltage)



Features


- > Linkable up to 200W.
- > Aluminum housing allows for excellent heat dissipation.
- > 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations.
- > Patent Male-female linkable design.

add your accessories\*

Accessories Part Number	Description
GI-ACC-3PC	3' power cable with plug
GI-ACC-6PC	6' power cable with plug
GI-ACC-15CC	1.5' linking cable
GI-ACC-6CC	6' linking cable
GI-ACC-SUS-DT5	suspension kit
GI-ACC-MC-T8	magnetic clip

\*optional

Light Distribution Curve



other

Warranty	Weight	Case QTY
6 years	1.10lbs	20 pcs



Included accessories :

- \* screws & clips
- \* small connector
- \* power cords



Not all product variations listed on this page may be DLC qualified. Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification.



/greenignite  
@greenignite



www.greenignite.com



info@greenignite.com



1-877-560-3779