



specifications

Consumption	Lumen Output	CRI	Efficacy	SP	Ambient Temp (F)	L70 hours	Beam Angle	Material	THD	Standard Finish	IP Rating	Dimmable
12 W	780	> 90	65 lm / W	> 0.95	-4°- 104°	50,000	110°	durable aluminum body	< 14.21%	white	wet location	yes triac

select your downlight fixture

Part Number	Color Temp	Voltage	Included Accessories
GI-4RLK-5CCT65-ES5	 selectable	 120 V (dimmable)	spring clips

Select your accessories*

4" Trim Accessories Part Number		
Matte Black	Bronze	Satin Nickel
 GI-ACC-4RLKB	 GI-ACC-4RLKBR	 GI-ACC-4RLKN

*optional

other specifications

Dimensions	Warranty	Weight	Case QTY
light: 4.24" x 1.75" x 0.57" driver: 4.5" x 2.75" x 1.5"	6 years	0.72 lbs	12 pcs



- Features**
- Selectable (dip switch) color temperature allows you to choose having 2700K, 3000K, 3500K, 4000K or 5000K
 - Optional matte black trim
 - Aluminum junction box included

Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.

