

Que-2-TXT[™] Questions? scan to text us fast



8FT LINEAR T8 / T12 RETROFIT LED LAMP

MULTI-BASE, SECTIONAL LAMP



specifications Ambient Temp (F) CRI BASE Heat Sink L70 hours **Power Factor UL** listing FA8 1.02" (L) glass with damp location 40W 🗲 100-277 V 83 50,000 -4°- 113° >0.9 <20% 180° aluminum and shatterproof coating fully enclosed fixtures 94.49" (D) R17D select your lamp other Lumen Output Part Number Color Temp Efficacy Weight Case QTY 3500K 1.02 lbs 10 pcs 6 years 5,500 120 lm / w GI-8T8F-WD110GS-DBDW4 L N Support screws 4000K GI-8T8F-D110GS-DBDW4 5,500 120 lm / w also included LED Tube GI-8T8F-C110GS-DBDW4 5,500 120 lm / w 5000K LED Tube Double-ended input MAGNETIC SUPPORT CLIP INCLUDED (t) FC 🕮 Luminous Intensity Distribution Spectogram **Features** Luminous in (unit:cd) 1.0 (2) 4ft lamps connect to form an 8ft lamp 4.5 > Shatterproof design. (glass with a shatterproof coating) 2.4 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations 4.1 Aluminum housing for excellent heat dissipation 1.7 Plug N' Play male and female connectors with 0.0 100 CI HI - 500 140 180 420 140 760 2.65 magnetic support clip Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.



0



