

Specifications

CRI	Ambient Temp (F)	Voltage	Housing & Lens	Lamp Head	IP Rating	Efficacy	Run Time	Warranty	Case Quantity
80	-20° - 40°	battery: 10.8V charger: AC100-240V	polycarbonate	aluminum alloy	lamp head & power box: IP65 housing: IP20	82 LM / W	10 hours	6 years	1 pcs

select your fixture

Part Number	Color Temp	Consumption	Lumen Output	Dimensions	Beam Angle
GI-Epra-C200-C1D1	5000K	19.5W / 5W selectable	1,600lm / 410lm	14" x 8.1"	125°

battery

Battery Type	Battery Capacity	Battery Lifespan	Change Time	Change Voltage
Ni-MH	10.8V, 9Ah	500 cycles	7 hours (1.8A) 14 hours (0.9A)	DC10.8V-14.4V


Included accessories


Accessories Part Number	Description
1.) GI-ACC-EPRAC	charger


Optional accessories

Accessories Part Number	Description
2.) GI-ACC-EPRAB	replacement battery

Certifications

 ATEX Marking:
II 1G Ex ia IIC T4 Ga

 IECEx Marking:
Ex ia IIC T4 Ga

 UL913 Marking (North American):
Class I, Division 1, Groups A, B, C and D, T4
Ex ia IIC T4 Ga
Class I, Zone 0, AEx ia IIC T4 Ga

Housing: IP20
Lamp head and power box: IP65
IK08

Features

- > 3 power settings: 19.5W, 5W & emergency flashing (hold power button for 10 seconds to activate)
- > Rated for high temperatures, humidity, dust and vapor locations
- > Low battery warning light - indicates at 30 mins left
- > 0-10V Dimmable
- > Multiple deployment positions
- > Deployable mast with 360° rotation
- > 10kVA Surge protection



Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.