




Que-2-TXT™
Questions?
scan to text us fast



HIGH BAY UFO LED FIXTURES



ROUND

specifications

Lens	CRI	Finish	Material	L70 hours	Surge Protection	Ambient Temp (F)	Power Factor	UL listing	THC	Distribution	Dimensions
frosted	72	white polyester powder-coat finish	durable, die-cast aluminum housing with heat dissipating fins	50,000	10 KV optional	-40° - 131°	> 0.9	wet location IP 66	<20%	IESNA type III	15.5" (D) x 4.5" (H)

select your lamp

Part Number	Color Temp	Voltage	Consumption	Lumen Output	Efficacy
GI-HBUM-C750-UL4	5000K	100 - 277 V ⚡	180 W	24,500	136 LM / W

add your accessories*

Accessories Part Number	Description
GI-ACC-OCC	occupancy sensor
GI-ACC-UFOBEB	emergency battery back up kit

other


Warranty	Weight	Case QTY
6 years	9.5 lbs	1 pc



Features

- Sealed die-casting profile for indoor and outdoor applications.
- 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations
- Thin profile, varsetile applications

Luminous Intensity Distribution



Distance vs Illumination

Dist(m)	Enadir(klx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(klx)
2.0	1848.87	6.36/6.38	32.4	278.02
4.0	462.22	12.71/12.76	129.5	69.50
6.0	205.43	19.07/19.14	291.3	30.89
8.0	115.55	25.43/25.52	517.9	17.38
10.0	73.95	31.79/31.90	809.2	11.12
12.0	51.36	38.14/38.28	1165.3	7.72
14.0	37.73	44.50/44.66	1586.0	5.67
16.0	28.89	50.86/51.04	2071.6	4.34
18.0	22.83	57.22/57.42	2621.8	3.43
20.0	18.49	63.57/63.80	3236.8	2.78

Dv Beam Angle(B): H115.6 V115.8 Field Angle(F): H171.6 V171.6

Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.



/greenignite
@greenignite

www.greenignite.com

info@greenignite.com

1-877-560-3779