



specifications

Consumption	Voltage	Efficacy	Material	Finish	Ambient Temp (F)	L70 hours	Beam Angle	CRI	PF	THD	IP Rating
50W/40W/30W/20W Power Selectable	120 - 277 V ⚡	140 lm /W	die-cast aluminum body, stainless steel cage	yellow powder-coat	-31°-131°	50,000	30°	> 70	> 0.9	< 20%	65 wet location

Part Number	Color Temp	Lumen Output
GI-LDL-D500-PSG4	4000K	50W - 7,000 LM 40W - 5,600LM 30W - 4,200 LM 20W - 2,800 LM



Choose your mount**

Part Number	Description
GI-ACC-DLAS	Single arm 
GI-ACC-DLAD	Double arm 

**optional

other specifications

Dimensions	Warranty
8.62" x 4.42" x 2.76"	6 years



Features

- 11.81" Power cord
- Electrical outlet embedded in the arm for direct plug in connection.
- Compact design utilizes aluminum housing, which dissipates heat for maximum lifespan.
- Frosted polycarbonate cover combats glare, and makes for more uniform lighting.
- Built-in on-off switch for convenience.



Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.

