

Que-2-TXT™ Questions? scan to text us fast



HID EQUAL LED RETROFIT KITS **REPLACES 1,500W HID**




specifications


CRI	Material	L70 hours	Surge Protection	Ambient Temp (F)	Power Factor	IP rating	Dimmable	THD	Beam Angle	Enclosed Fixture Rated
> 70	aluminum	50,000	6 KV built-in	-40° - 122º	> 0.9	IP 44	1 - 10%	6.21%	114º	yes
select your lamp					other					

Part Number	Color Temp	Voltage	Lumen Output	Efficacy	Consumption
GI-RKD-D1500-DLC	5000K	100 - 277 V 🗲	60,000	125 lm / W	480W
GI-RKD-C1500-480DLC	5000K	277 - 480 V 🗲	56,250	125 lm / W	450W

Fixture Dimensions	Driver Dimensions	Warranty	Gross Weight	Case QTY
12.6" (L) x 3.35" (H)	8 3/4" (L) x 1.5" (H) x 2 5/8" (W)	6 years	12.56 lbs	1 pcs

Features External Driver 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations Allows for reflector to be removed to create more space for installation Adjustable bracket included







Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.













